

OGAN[®]
Heating hose technology

Melton compatible
Hot melt hoses



CE

Melton Compatible heated hose

OGAN Heating Hoses developed and produced for Melton glue systems are produced from hi-tech components. OGAN Heating Hoses are highly flexible for manual hand gun and robotic applications and extra strengthened to prevent external and internal structural deformation which may occur from dynamic movements.

- 100% compliant with Melton systems,
- High quality PTFE hose have a continuous working temperature of 260 °C and a burst pressure of 4 times the working pressure,
- PTFE heavy-duty teflon internal structure is resistant to all solvents, acids and aggressive adhesives under high temperature operating conditions,
- Guarantees long lifetime when installed and used according to the instructions,
- Available with the ID 6 , 8 , 13 , 16 , 20 ,25,32,40 mm and any length between 0.4 m – 20 m.
- Available in Standard, High-Pressure and Water-Protected versions. Please refer to below tables.
- Can also be produced based on your specific requests.



DN8	Ni120	230 V	230 °C
Length	MELTON P/N		OGAN P/N
0,60 m	981xx001		M-981xx001
0,80 m	981xx002		M-981xx002
1,20 m	981xx003		M-981xx003
1,40 m	981xx004		M-981xx004
1,80 m	981xx005		M-981xx005
2,40 m	981xx006		M-981xx006
3,00 m	981xx007		M-981xx007
3,60 m	981xx008		M-981xx008
4,80 m	981xx010		M-981xx010
5,40 m	981xx011		M-981xx011
6,00 m	981xx012		M-981xx012
7,20 m	981xx013		M-981xx013
8,00 m	981xx014		M-981xx014
9,00 m			M-981xx090
10,00 m	981xx015		M-981xx015
12,00 m			M-981xx120



DN13	Ni120	230 V	230 °C
Length	MELTON P/N		OGAN P/N
0,60 m	981xx201		M-981xx201
1,20 m	981xx202		M-981xx202
1,80 m	981xx203		M-981xx203
2,40 m	981xx204		M-981xx204
3,00 m	981xx205		M-981xx205
3,60 m	981xx206		M-981xx206
4,20 m	981xx207		M-981xx207
4,80 m	981xx208		M-981xx208
6,00 m	981xx209		M-981xx209
7,20 m	981xx210		M-981xx210
8,00 m	981xx211		M-981xx211
9,00 m			M-981xx290
10,00 m	981xx212		M-981xx212
12,00 m			M-981xx220



DN20	Ni120	230 V	230 °C
Length	MELTON P/N		OGAN P/N
0,60 m	981xx241		M-981xx241
1,20 m	981xx242		M-981xx242
1,80 m	981xx243		M-981xx243
2,40 m	981xx244		M-981xx244
3,00 m	981xx245		M-981xx245
3,60 m	981xx246		M-981xx246
4,20 m	981xx247		M-981xx247
4,80 m	981xx248		M-981xx248
6,00 m	981xx249		M-981xx249
7,20 m	981xx250		M-981xx250
8,00 m	981xx251		M-981xx251
9,00 m			M-981xx390
10,00 m	981xx252		M-981xx252
11,00 m			M-981xx391
12,00 m			M-981xx392



DN8 WD	Ni120	230 V	230 °C
Length	MELTON P/N		OGAN P/N
0,60 m	981xx021		M-981xx021
1,20 m	981xx023		M-981xx023
1,80 m	981xx025		M-981xx025
2,40 m	981xx026		M-981xx026
3,00 m	981xx027		M-981xx027
3,60 m	981xx028		M-981xx028
4,80 m	981xx030		M-981xx030



DN8	PT100	230 V	230 °C
Length	MELTON P/N		OGAN P/N
0,60 m	981xx101		M-981xx101
0,80 m	981xx102		M-981xx102
1,20 m	981xx103		M-981xx103
1,40 m	981xx104		M-981xx104
1,80 m	981xx105		M-981xx105
2,40 m	981xx106		M-981xx106
3,00 m	981xx107		M-981xx107
3,60 m	981xx108		M-981xx108
4,20 m	981xx109		M-981xx109
4,80 m	981xx110		M-981xx110
5,40 m	981xx111		M-981xx111
6,00 m	981xx112		M-981xx112
7,20 m			M-981xx172
8,00 m	981xx113		M-981xx113
9,00 m			M-981xx190
10,00 m	981xx014		M-981xx014
12,00 m			M-981xx312



DN13	PT100	230 V	230 °C
Length	MELTON P/N		OGAN P/N
0,60 m	981xx221		M-981xx221
1,20 m	981xx222		M-981xx222
1,80 m	981xx223		M-981xx223
2,40 m	981xx224		M-981xx224
3,00 m	981xx225		M-981xx225
3,60 m	981xx226		M-981xx226
4,20 m	981xx227		M-981xx227
4,80 m	981xx228		M-981xx228
6,00 m	981xx229		M-981xx229
8,00 m	981xx230		M-981xx230
10,00 m	981xx231		M-981xx231



DN20	PT100	230 V	230 °C
Length	MELTON P/N		OGAN P/N
0,60 m	981xx261		M-981xx261
1,20 m	981xx262		M-981xx262
1,80 m	981xx263		M-981xx263
2,40 m	981xx264		M-981xx264
3,00 m	981xx265		M-981xx265
3,60 m	981xx266		M-981xx266
4,20 m	981xx267		M-981xx267
4,80 m	981xx268		M-981xx268
6,00 m	981xx269		M-981xx269
8,00 m	981xx270		M-981xx270
10,00 m	981xx271		M-981xx271
11,00 m			M-981xx411
12,00 m			M-981xx412



DN8 DM	Ni120	230 V	230 °C
Length	MELTON P/N		OGAN P/N
3,00 m	981xx081		M-981xx081
4,80 m	981xx082		M-981xx082
7,20 m	981xx083		M-981xx083
9,00 m	981xx084		M-981xx084

DN16 DM	Ni120	230 V	230 °C
3,00 m	981xx091		M-981xx091
4,80 m	981xx092		M-981xx092
7,20 m	981xx093		M-981xx093
9,00 m	981xx094		M-981xx094

DN8	Ni120	230 V	230 °C
Length	MELTON P/N		OGAN P/N
0,60 m	981xx941		M-981xx941
1,20 m	981xx942		M-981xx942
1,80 m	981xx943		M-981xx943
2,40 m	981xx944		M-981xx944
3,00 m	981xx945		M-981xx945

DN8 AD31	Ni120	230 V	230 °C
Length	MELTON P/N		OGAN P/N
2,40 m	981xx098		M-981xx098
3,00 m	981xx097		M-981xx097



DN8 RB	NTC	230 V	230 °C
Length	MELTON P/N		OGAN P/N
1,20 m	982xx203		M-982xx203
1,50 m	982xx204		M-982xx204
1,80 m	982xx205		M-982xx205
2,00 m	982xx206		M-982xx206
2,50 m	982xx207		M-982xx207
3,00 m	982xx208		M-982xx208
4,00 m	982xx209		M-982xx209
5,00 m	982xx210		M-982xx210





Headquarters

Ogan Endustriyel Isi Hortum San. Ltd. Sti.

Deri OSB 3 Nolu Giris, Yan Sanayi Cad.

Biye Sok. No:31 Aydinli

Tuzla 34953 İstanbul, Turkey

Tel: +90 216 591 0343

+90 533 469 1009 (for English)

e-mail: info@ogan.com.tr

foreigntrade@ogan.com.tr (for English)

Web: www.ogan.com.tr

UK Distributor

Hot Melt Services Ltd.

Unit 3, Wymeswold Industrial Park,

Burton On The Wolds,

Loughborough, LE12 5TR United Kingdom.

Tel: 01509 889 511

e-mail: services@hotmeltservices.com

Web: <https://hotmeltservices.com>